

KITCHEN ARMOR

21.5" PCAP Touch Display

KA-22FMJEL01



Kitchen Armor's 21.5" projected capacitive displays are purpose built for use in kitchen applications or wherever you need a rugged and durable touch screen to stand up to the elements. The flat working surface and stainless steel full metal jacket design eliminates the worry of grease and food buildup, which helps protect and extend the life of your touch screen monitor.

Features:

- Stainless Steel touch screen display
- Easy to clean (water, grease and food resistant)
- Rapid and smooth touch response
- Excellent optical performance
- Zero pressure touch activation
- VESA 100mm mounting

Benefits:

- PCAP technology allows for touch to work with gloved hands
- Maintenance free, longer life expectancy
- Operable in various light conditions

KITCHEN ARMOR

21.5" PCAP Touch Display

KA-22FMJELO1



Kitchen Armor KA-22FMJELO1 Specifications

| | |
|------------------------------|---|
| Screen Size | 21.5" |
| Touch Technology | PCAP |
| Mounting Options | VESA 100mm, 4" : 105mm from top |
| Aspect Ratio | 16:9 |
| Dimensions (W x H x D in:mm) | 20.5" x 12.3" x 1.6" : 520.7 x 312.42 x 40.64 |
| Active Display Area (in: mm) | 18.76" (H) x 10.55" (V) : 476.6 (H) x 268.1 (V) |
| Color Depth | 16.7M |
| Resolution | 1920 x 1080 @ 50, 60Hz |
| Response Time (typ) | 5ms |
| Brightness (cd/m2) | 250 |
| Contrast Ratio (typ) | 1000:1 |
| Viewing Angle (typ) | 85°/170°(H) 80°160°(V) |
| Display Interface (typ) | VGA, Display Port |
| Touch Screen Interface | USB |
| Power Supply Input Voltage | DC:12V; External power adapter |
| Power Consumption (typ) | 18W |
| OSD | Contrast, Brightness, Clock, Phase, Horizontal vertical image size and position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, Language selection, RECALL function, Video Priority, Information, Touch On Sleep Mode, Touch Through |
| Operating Temperature | 0°C - 45°C ; Storage: -20°C - 60°C |
| Operating Humidity | 20% - 80%; Storage: 10% - 95% |
| Certifications | UL, FCC, RCM, cUL, IC, CCC, CE, TUV, VCCI, KCC, CoC, BSMI, CB, RoHS, China RoHS, WEEE, IMERC |
| Warranty | 3 Years |