

KITCHEN ARMOR



21.5" PCAP Android All-in-One KA-22PCAPAI03

Full Stainless Steel Design

Product Overview

The Kitchen Armor 22 inch Android all-in-one kitchen station is designed for restaurant application to provide many years of service. Power Over Ethernet (POE) saves the expense of electrical outlets and provides ease in setup and trouble shooting, while making station sleek and clean.

Kitchen Armor's stainless steel full metal jacket is designed for use in restaurants and industrial kitchens. This commercial grade appliance provides extended life for the professional kitchen environment and is easily maintained to prevent grease and food buildup, keeping your line pristine.

Features

- Stainless steel design
- Industrial Enclosure
- POE+
- Sleek all-in-one design

Benefits

- Easy to clean
- Dust, water, and grease resistant
- Reduced installation cost
- Excellent optical performance



Integrated Touch



Restaurant Approved



Commercial Grade

21.5" PCAP Android All-in-One Specifications

| Item | Specifications |
|----------------------------------|--|
| Model | KA-22PCAPAI03 |
| Finish | Stainless Steel |
| Touch Technology | PCAP |
| Dimensions | 20.83" x 12.6" x 1.94" / 529 mm x 320 mm x 49.2 mm |
| Active Display Area | 18.77" x 10.56" / 476.64 mm x 268.11 mm |
| Diagonal, Aspect Ratio | 21.5", 16:9 |
| Mounting Options | 100 mm VESA mount |
| Color Depth | 16.7 Million |
| Resolution | Native: 1920x1080 at 60Hz |
| Pixel Pitch | 0.24825 mm x 0.24825 mm |
| Contrast Ratio, Brightness (TYP) | 3000:1, 250 nits |
| Response Time (TYP) | 18 msec |
| Viewing Angle (TYP) | Horizontal: 89° or 178° total; Vertical: 89° or 178° total |
| Touch Capacity, Accuracy | 10-touch, 2 mm |
| Touch Response Time | 10 msec |
| Minimum Touch Body | Ø7 mm |
| Touch Activation Force | 10 g |
| Touch Resolution | 4096x4096 |
| Input Method | Finger, Touch Pen, Gloved Hand |
| Material | 3.0 mm strengthen glass |
| Surface Durability | Mohs' 7H |
| Weight | 16.3 lbs / 7.39 kgs |
| Packing Weight | 20 lbs / 9.07 kgs |
| Packing Dimensions | 25.5" x 18" x 7" / 647.7 mm x 457.2 mm x 177.8 mm |
| Light Transmission | 86% |
| CPU | RK3399 |
| Flash | 16G |
| RAM | 4G |
| OS | Android 7.1.2 |
| WIFI | 2.4GHZ/5GHZ |
| Bluetooth | 4.1 |
| LAN | Ethernet 1xRJ45 (100/10 Mbps) |
| Power Supply | POE+/External 12V DC Power Adapter |
| POE+ Power Requirements | Switch must meet 802.3at (POE+) 30 Watts, Minimum Cat 5e Cable, 24ga |
| Lighted Power Switch | Power with LED light: Blue Light |
| Speaker | 3 Watts |
| Temperature | Operating: 0°C to 40°C (32°F to 104°F); Storage: -20°C to 60°C (-4°F to 140°F) |
| Humidity | Operating: 20% to 80%; Storage: 10% to 90% |
| IP | IP 65 |
| MTBF | 50,000 hours/50,000,000 touches |
| Certification | CE, FCC |
| Warranty | 1 year, extendable up to 3 years |

Version 2.4.2021

